

INSTALLATION INSTRUCTIONS

WHITE = LEFT Front (+) Input
WHITE /BLACK = LEFT Front (-) Input
GRAY = RIGHT Front (+) Input
GRAY/BLACK= RIGHT Front (-) Input
GREEN= LEFT Rear (+) Input
GREEN/BLACK = LEFT rear (-) Input
PURPLE= RIGHT Rear (+) Input,
PURPLE/BLACK = RIGHT Rear (-) Input
BLACK = Reference Ground (-)

NOTE: Be sure that all audio input connections are polarized or in phase with each other. That is, the positive output wires from the audio source need to be connected to the corresponding positive input wires of the AX-ALOC658. The same goes for the negative audio wires. Failure to do this will result in poor bass response and low quality audio.

After completing all of the necessary connections turn the AX-ALOC658 adjustment pots all of the way down by rotating them completely counter-clockwise. Now, turn the stereo system on and adjust the main volume control on the stereo to approximately 3/4 maximum volume. Select one of the adjustment pots on the AX-ALOC658 and turn it slowly clockwise until you notice audio distortion and then stop. Turn the remaining pot to the same position as the previously adjusted pot. The audio set-up of the AX-ALOC658 is now complete and ready to be enjoyed.

INSTALLATION INSTRUCTIONS

WHITE = LEFT Front (+) Input
WHITE/BLACK = LEFT Front (-) Input
GRAY = RIGHT Front (+) Input
GRAY/BLACK = RIGHT Front (-) Input
GREEN = LEFT Rear (+) Input
GREEN/BLACK = LEFT rear (-) Input
PURPLE = RIGHT Rear (+) Input
PURPLE/BLACK = RIGHT Rear (-) Input
BLACK = Reference Ground (-)

NOTE: Be sure that all audio input connections are polarized or in phase with each other. That is, the positive output wires from the audio source need to be connected to the corresponding positive input wires of the AX-ALOC658. The same goes for the negative audio wires. Failure to do this will result in poor bass response and low quality audio.

After completing all of the necessary connections turn the AX-ALOC658 adjustment pots all of the way down by rotating them completely counter-clockwise. Now, turn the stereo system on and adjust the main volume control on the stereo to approximately 3/4 maximum volume. Select one of the adjustment pots on the AX-ALOC658 and turn it slowly clockwise until you notice audio distortion and then stop. Turn the remaining pot to the same position as the previously adjusted pot. The audio set-up of the AX-ALOC658 is now complete and ready to be enjoyed.

INSTALLATION INSTRUCTIONS

WHITE = LEFT Front (+) Input
WHITE/BLACK = LEFT Front (-) Input
GRAY = RIGHT Front (+) Input
GRAY/BLACK= RIGHT Front (-) Input
GREEN= LEFT Rear (+) Input
GREEN/BLACK = LEFT rear (-) Input
PURPLE= RIGHT Rear (+) Input,
PURPLE/BLACK = RIGHT Rear (-) Input
BLACK = Reference Ground (-)

NOTE: Be sure that all audio input connections are polarized or in phase with each other. That is, the positive output wires from the audio source need to be connected to the corresponding positive input wires of the AX-ALOC658. The same goes for the negative audio wires. Failure to do this will result in poor bass response and low quality audio.

After completing all of the necessary connections turn the AX-ALOC658 adjustment pots all of the way down by rotating them completely counter-clockwise. Now, turn the stereo system on and adjust the main volume control on the stereo to approximately 3/4 maximum volume. Select one of the adjustment pots on the AX-ALOC658 and turn it slowly clockwise until you notice audio distortion and then stop. Turn the remaining pot to the same position as the previously adjusted pot. The audio set-up of the AX-ALOC658 is now complete and ready to be enjoyed.

INSTALLATION INSTRUCTIONS

WHITE = LEFT Front (+) Input
WHITE/BLACK = LEFT Front (-) Input
GRAY = RIGHT Front (+) Input
GRAY/BLACK = RIGHT Front (-) Input
GREEN = LEFT Rear (+) Input
GREEN/BLACK = LEFT Rear (-) Input
PURPLE = RIGHT Rear (+) Input,
PURPLE/BLACK = RIGHT Rear (-) Input
BLACK = Reference Ground (-)

NOTE: Be sure that all audio input connections are polarized or in phase with each other. That is, the positive output wires from the audio source need to be connected to the corresponding positive input wires of the AX-ALOC658. The same goes for the negative audio wires. Failure to do this will result in poor bass response and low quality audio.

After completing all of the necessary connections turn the AX-ALOC658 adjustment pots all of the way down by rotating them completely counter-clockwise. Now, turn the stereo system on and adjust the main volume control on the stereo to approximately 3/4 maximum volume. Select one of the adjustment pots on the AX-ALOC658 and turn it slowly clockwise until you notice audio distortion and then stop. Turn the remaining pot to the same position as the previously adjusted pot. The audio set-up of the AX-ALOC658 is now complete and ready to be enjoyed.

INSTALLATION INSTRUCTIONS

WHITE = LEFT Front (+) Input
WHITE /BLACK = LEFT Front (-) Input
GRAY = RIGHT Front (+) Input
GRAY/BLACK= RIGHT Front (-) Input
GREEN= LEFT Rear (+) Input
GREEN/BLACK = LEFT rear (-) Input
PURPLE= RIGHT Rear (+) Input,
PURPLE/BLACK = RIGHT Rear (-) Input
BLACK = Reference Ground (-)

NOTE: Be sure that all audio input connections are polarized or in phase with each other. That is, the positive output wires from the audio source need to be connected to the corresponding positive input wires of the AX-ALOC658. The same goes for the negative audio wires. Failure to do this will result in poor bass response and low quality audio.

After completing all of the necessary connections turn the AX-ALOC658 adjustment pots all of the way down by rotating them completely counter-clockwise. Now, turn the stereo system on and adjust the main volume control on the stereo to approximately 3/4 maximum volume. Select one of the adjustment pots on the AX-ALOC658 and turn it slowly clockwise until you notice audio distortion and then stop. Turn the remaining pot to the same position as the previously adjusted pot. The audio set-up of the AX-ALOC658 is now complete and ready to be enjoyed.

INSTALLATION INSTRUCTIONS

WHITE = LEFT Front (+) Input
WHITE/BLACK = LEFT Front (-) Input
GRAY = RIGHT Front (+) Input
GRAY/BLACK = RIGHT Front (-) Input
GREEN = LEFT Rear (+) Input
GREEN/BLACK = LEFT rear (-) Input
PURPLE = RIGHT Rear (+) Input
PURPLE/BLACK = RIGHT Rear (-) Input
BLACK = Reference Ground (-)

NOTE: Be sure that all audio input connections are polarized or in phase with each other. That is, the positive output wires from the audio source need to be connected to the corresponding positive input wires of the AX-ALOC658. The same goes for the negative audio wires. Failure to do this will result in poor bass response and low quality audio.

After completing all of the necessary connections turn the AX-ALOC658 adjustment pots all of the way down by rotating them completely counter-clockwise. Now, turn the stereo system on and adjust the main volume control on the stereo to approximately 3/4 maximum volume. Select one of the adjustment pots on the AX-ALOC658 and turn it slowly clockwise until you notice audio distortion and then stop. Turn the remaining pot to the same position as the previously adjusted pot. The audio set-up of the AX-ALOC658 is now complete and ready to be enjoyed.

AX-ALOC658

4 CHANNEL, ADJUSTABLE LINE OUTPUT CONVERTER

The **AX-ALOC658** is designed to convert 4 channels of speaker level audio to line level audio. This allows for the installation of line level products such as amplifiers, EQs and crossovers on stereo heads that do not have RCA line level outputs.

Features:

150 Watts Maximum Input, Input Circuit Corrects crossover distortion commonly found on other brands of locs, 3:1 step down with variable output, detachable input plug, gold flashed rcas, attractive & durable enclosure.



1-800-221-0932

axxessinterface.com

© COPYRIGHT 2004-2010 METRA ELECTRONICS CORPORATION

AX-ALOC658

4 CHANNEL, ADJUSTABLE LINE OUTPUT CONVERTER

The **AX-ALOC658** is designed to convert 4 channels of speaker level audio to line level audio. This allows for the installation of line level products such as amplifiers, EQs and crossovers on stereo heads that do not have RCA line level outputs.

Features:

150 Watts Maximum Input, Input Circuit Corrects crossover distortion commonly found on other brands of locs, 3:1 step down with variable output, detachable input plug, gold flashed rcas, attractive & durable enclosure.



1-800-221-0932

axxessinterface.com

© COPYRIGHT 2004-2010 METRA ELECTRONICS CORPORATION

AX-ALOC658

4 CHANNEL, ADJUSTABLE LINE OUTPUT CONVERTER

The **AX-ALOC658** is designed to convert 4 channels of speaker level audio to line level audio. This allows for the installation of line level products such as amplifiers, EQs and crossovers on stereo heads that do not have RCA line level outputs.

Features:

150 Watts Maximum Input, Input Circuit Corrects crossover distortion commonly found on other brands of locs, 3:1 step down with variable output, detachable input plug, gold flashed rcas, attractive & durable enclosure.



1-800-221-0932

axxessinterface.com

© COPYRIGHT 2004-2010 METRA ELECTRONICS CORPORATION

AX-ALOC658

4 CHANNEL, ADJUSTABLE LINE OUTPUT CONVERTER

The **AX-ALOC658** is designed to convert 4 channels of speaker level audio to line level audio. This allows for the installation of line level products such as amplifiers, EQs and crossovers on stereo heads that do not have RCA line level outputs.

Features:

150 Watts Maximum Input, Input Circuit Corrects crossover distortion commonly found on other brands of locs, 3:1 step down with variable output, detachable input plug, gold flashed rcas, attractive & durable enclosure.



1-800-221-0932

axxessinterface.com

© COPYRIGHT 2004-2010 METRA ELECTRONICS CORPORATION

AX-ALOC658

4 CHANNEL, ADJUSTABLE LINE OUTPUT CONVERTER

The **AX-ALOC658** is designed to convert 4 channels of speaker level audio to line level audio. This allows for the installation of line level products such as amplifiers, EQs and crossovers on stereo heads that do not have RCA line level outputs.

Features:

150 Watts Maximum Input, Input Circuit Corrects crossover distortion commonly found on other brands of locs, 3:1 step down with variable output, detachable input plug, gold flashed rcas, attractive & durable enclosure.



1-800-221-0932

axxessinterface.com

© COPYRIGHT 2004-2010 METRA ELECTRONICS CORPORATION

AX-ALOC658

4 CHANNEL, ADJUSTABLE LINE OUTPUT CONVERTER

The **AX-ALOC658** is designed to convert 4 channels of speaker level audio to line level audio. This allows for the installation of line level products such as amplifiers, EQs and crossovers on stereo heads that do not have RCA line level outputs.

Features:

150 Watts Maximum Input, Input Circuit Corrects crossover distortion commonly found on other brands of locs, 3:1 step down with variable output, detachable input plug, gold flashed rcas, attractive & durable enclosure.



1-800-221-0932

axxessinterface.com

© COPYRIGHT 2004-2010 METRA ELECTRONICS CORPORATION